

F77 SUPER STREET RECON

30 KW
PEAK POWER
(Electrical Power)

155 KM/H
MAX SPEED
(Company Tested)

100 NM
PEAK MOTOR
TORQUE

231 KM
CITY RANGE
(WMTC)



DESIGN
AERO SURFACES



Afterburner Yellow



Turbo Red



Cosmic Black



Stellar White

F SERIES -
JET INSPIRED
DESIGN SERIES

DYNAMIC,
STREET-ORIENTED
STANCE

PARALLAX &
RADAR
CONSOLE THEMES

PERFORMANCE

POWER

30 KW

PEAK POWER
[Electrical Power]

20 KW

NET POWER
[ECE R85]

9.5 KW @ 3000 RPM

CONTINUOUS POWER [ECE R85]

TORQUE

100 NM

PEAK MOTOR TORQUE

SPEED

155 KM/H

MAX. SPEED
[Company tested]

144 KM/H

TOP SPEED
[ECE R39.01]

ACCELERATION

2.8 SEC

0-60 KM/H

7.7 SEC

0-100 KM/H

REGENERATIVE BRAKING

10 LEVELS

**DYNAMIC
REGEN**

RIDE MODES

GLIDE, COMBAT, BALLISTIC

REQUIRED LICENSE

A1

RANGE

231 KM

CITY RANGE
[As per WMTTC]

143 KM

HIGHWAY RANGE
[As per WMTTC]

SMART TECH

VIOLETTE A.I.

DELTA WATCH Optional

LOCKDOWN Optional

ANTI-COLLISION WARNING SYSTEM Optional

CRASH ALERT Optional

DAILY RIDE ANALYTICS Optional

CONTROL CENTER Multi-function 5" TFT display with tactile input switch console (L+R)

OPERATING SYSTEM UV Automotive Linux OS

SAFETY

Auto dimming LED Headlight with Ultra-V position lamp

Dual LED tail light assembly with central brake light

Front and Rear LED Hazard Lights

Sidestand Sensor

TRACTION CONTROL 4 levels

HILL HOLD Included

ABS Mono & Dual Channel

D.S.C - DYNAMIC STABILITY CONTROL Included

UTILITY

CHARGE LIMIT	Included
PARK ASSIST	Included
FIND MY F77	Included
DEEP SLEEP	Included
TPMS	Included

BATTERY SYSTEM

BATTERY PACK	SRB10
ENERGY CAPACITY	10.3 kWh
ENCLOSURE	All-Aluminum IP67-rated enclosure
BMS & SAFETY PROTOCOLS	Battery Management System with patented 5-level safety system - Mechanical, Thermal, Electrical, Electronic & Software protection

BATTERY & DRIVETAIN WARRANTY

UV CARE	5 years or 100.000 km included
---------	--------------------------------

VEHICLE WARRANTY

STANDARD WARRANTY (VEHICLE)	3 years or 30.000 km included
-----------------------------	-------------------------------

CHARGING

CHARGING PORT

IEC 62196-6

BOOST CHARGER

Included

CHARGE RATE

20% - 80% in 2.5 hrs

DRIVETRAIN

MOTOR

Permanent Magnet AC Motor

THROTTLE CONTROL

Ride-by-wire

MECHANICAL

FRAME

Steel Trellis with Aluminium Bulk Head

FRONT SUSPENSION

Upside-down Telescopic fork with a diameter of 41 mm. Preload adjustable

REAR SUSPENSION

Monoshock - preload adjustable

BRAKE SYSTEM

Hydraulic disc brakes with dual-channel BOSCH ABS

BRAKE CALIPERS

Front: Fixed 4-Radial Piston Type
Rear: Single Piston Floating Caliper Type

BRAKE ROTOR

Front: 320mm disc Rear: 230mm disc

TYRES

Front: 110/70 R17 Rear: 150/60 R17

CONNECTIVITY

NETWORK

LTE connectivity with integrated eSIM

WLAN

Supports 802.11a/b/g/n/ac Wi-Fi standards

BLUETOOTH

Supports Bluetooth 5, Bluetooth low energy

POSITIONING

GPS/GLONASS

DIMENSIONS

WHEEL BASE

1340 mm

SEAT HEIGHT

800 mm

KERB WEIGHT

207 kg

GROUND CLEARANCE

160 mm