

MACH = SPEC SHEET

 π +

DESIGN

AERO SURFACES

MACH 2

MACH 2 RECON

LASER







Turbo Red

Plasma Red

Afterburner Yellow

SHADOW







Stealth Grey

Asteroid Grey

Cosmic Black

AIRSTRIKE







Supersonic Silver

Stellar White

Lightning Blue

DESIGN SERIES F series - Jet Inspired F series - Jet Inspired

STANCE Dynamic, Race bred Dynamic, Race bred

CONSOLE THEMES Parallax & Radar Parallax & Radar

PERFORMANCE

PEAK POWER 27 kW (36.2 hp) 30 kW (40.2 hp)

PEAK TORQUE 90 Nm 100 Nm

MAX SPEED 155 km/h 155 km/h

ACCELERATION (0-60 KMPH) 2.9 sec 2.8 sec

ACCELERATION (0-100 KMPH) 7.8 sec 7.7 sec

DYNAMIC REGENERATIVE BRAKING Included Included

LEVELS OF REGENERATIVE BRAKING 3 levels included 10 levels

10 levels optional

RIDE MODES Glide, Combat, Ballistic Glide, Combat, Ballistic

RANGE ESTIMATES

RANGE (IDC EST.) 211 km 323 km

 RANGE GLIDE (AVG. 40 WH/KM)
 183 km
 266 km

 RANGE COMBAT (AVG. 52 WH/KM)
 144 km
 209 km

RANGE BALLISTIC (AVG. 60 WH/KM) 128 km **186 km**





MACH 2 MACH 2 RECON

SMART TECH		
VIOLETTE A.1.	Optional	Optional
DELTA WATCH	Optional	Optional
LOCKDOWN	Optional	Optional
ANTI-COLLISION WARNING SYSTEM	Optional	Optional
CRASH ALERT	Optional	Optional
DAILY RIDE ANALYTICS	Optional	Optional
CONTROL CENTER	Multi-function 5" TFT display with tactile input switch console (L+R)	Multi-function 5" TFT display with tactile input switch console (L+R)
OPERATING SYSTEM	UV Automotive Linux OS	UV Automotive Linux OS
SAFETY	Auto dimming LED Headlight with Ultra-V position lamp	Auto dimming LED Headlight with Ultra-V position lamp
	Dual LED tail light assembly with central brake light	Dual LED tail light assembly with central brake light
	Front and Rear LED Hazard Lights	Front and Rear LED Hazard Lights
	Sidestand Sensor	Sidestand Sensor
TRACTION CONTROL	Optional	4 levels
HILL HOLD	Included	Included
ABS	Mono & Dual channel	Mono & Dual channel
D.S.C - DYNAMIC STABILITY CONTROL	Included	Included
UTILITY		
CHEILI		

CHARGE LIMIT	Included	Included
PARK ASSIST	Included	Included
FIND MY F77	Included	Included
DEEP SLEEP	Included	Included
TPMS	Optional	Optional





MACH 2

MACH 2 RECON

Patented 5-level Safety System -

Mechanical, Thermal, Electrical,

Electronic & Software Protection

+ \times π

BATTERY SYSTEM

BATTERY PACK SRB7 SRB10

7.1 kWh 10.3 kWh **ENERGY CAPACITY**

Battery Management System with Battery Management System with **BMS & SAFETY PROTOCOLS**

> Patented 5-level Safety System -Mechanical, Thermal, Electrical, Electronic & Software Protection

ENCLOSURE All-Aluminum IP67-rated Enclosure All-Aluminum IP67-rated Enclosure

BATTERY & DRIVETRAIN WARRANTY

UV CARE 3 years or 60,000 km included

5 years or 1,00,000 km included 5 years or 1,00,000 km optional **UV CARE PLUS**

UV CARE MAX N/A 8 years or 8,00,000 km optional

VEHICLE WARRANTY

STANDARD WARRANTY (VEHICLE) 3 years or 30,000km* 3 years or 30,000km*

CHARGING

IEC 62196-6 IEC 62196-6 **CHARGING PORT**

UV SUPERNOVA PLUS Compatible Compatible

(12KW DC FAST CHARGING NETWORK) 20% - 80% in 45 min 20% - 80% in 60 min

STANDARD **CHARGER**

Included

charge

CHARGE RATE Up to 35 km of range per hour of Up to 35 km of range per hour of

charge

20% - 80% in 3 hrs 20% - 80% in 5 hrs

Included

charge

Optional

BOOST CHARGER Optional

CHARGE RATE Up to 75 km of range per hour of Up to 75 km of range per hour of

charge

20% - 80% in 1.5 hrs 20% - 80% in 2.5 hrs





MACH 2

MACH 2 RECON

channel BOSCH ABS

standards

energy

Single Piston Floating Caliper Type

トメオ

DRIVETRAIN

MOTOR Permanent Magnet AC Motor Permanent Magnet AC Motor

THROTTLE CONTROL Ride-by-wire Ride-by-wire

MECHANICAL

Steel Trellis with Aluminium Bulk Head Steel Trellis with Aluminium Bulk Head **FRAME**

Upside-down Telescopic fork with a Upside-down Telescopic fork with a FRONT SUSPENSION diameter of 41 mm. Preload adjustable diameter of 41 mm. Preload adjustable

Monoshock - preload adjustable **REAR SUSPENSION** Monoshock - preload adjustable

Hydraulic disc brakes with dual-**BRAKE SYSTEM** Hydraulic disc brakes with dual-

channel BOSCH ABS

BRAKE CALIPERS Front: Fixed 4-Radial Piston Type Rear: Front: Fixed 4-Radial Piston Type Rear:

Single Piston Floating Caliper Type

Front: 320mm disc Rear: 230mm disc Front: 320mm disc Rear: 230mm disc **BRAKE ROTOR**

Front: 110/70 R17 Rear: 150/60 R17 Front: 110/70 R17 Rear: 150/60 R17 **TYRES**

CONNECTIVITY

NETWORK LTE connectivity with integrated eSIM LTE connectivity with integrated eSIM

Supports 802.11a/b/g/n/ac Wi-Fi Supports 802.11a/b/g/n/ac Wi-Fi WLAN

standards

Supports Bluetooth 5, Bluetooth low Supports Bluetooth 5, Bluetooth low **BLUETOOTH**

energy

GPS/GLONASS POSITIONING GPS/GLONASS

DIMENSIONS

1340 mm 1340 mm WHEEL BASE

800 mm 800 mm **SEAT HEIGHT**

197 kg 207 kg KERB WEIGHT

160 mm 160 mm

GROUND CLEARANCE